16th World Meeting 87/27 NM

Evaluation of Road Safety in Portugal: A Case Study Analysis

Ana Fernandes José Neves

Instituto Superior Técnico











OUTLINE

- Objectives
- Methodology
- Results
 - Road environments
 - Expected number of road accidents
- Conclusions





OBJECTIVES

- PhD Research at Technical University of Lisbon
- Definition of different maintenance programmes for skid resistance and texture depth in different road environments
 - 1. Selection of roads
 - 2. Definition of road environments
 - 3. Modelling the expected value of road accidents
 - a. Evaluation of the influence of pavement surface characteristics on accident occurrence
 - b. Establishing threshold values for the International Friction Index (IFI), skid resistance and texture depth, according to safety criteria









RESULTS SELECTED ROADS

- 8 different roads (A to H) with a total length of 254 km, covering:
 - different road categories,
 - varied geographical distribution,
 - good and bad levels of pavement conditions and accidents.

Road	Region	Category	Extension (km)
A	Lisboa	Secondary Road	19
В	Castelo Branco	Secondary Road	21
C	Beja	Primary road	43
D	Évora	Secondary Road	15
E	Faro	Secondary Road	39
F	Castelo Branco	Primary road	25
G	Vila Real	Primary road	52
H	Bragança	Primary road	40



RESULTS ROAD ENVIRONMENTS

• 7 different road environments

Variablas	Cluster 1	Cluster 2	Cluster 3	Cluster 4	Cluster 5	Cluster 6	Cluster 7	Moon	Standard
variables	(RE1)	(RE2)	(RE3)	(RE4)	(RE5)	(RE6)	(RE7)	wean	Deviation
%H_TRAF	26%	4%	8%	7%	10%	9%	9%	10%	6%
AV_SP (km/h)	81	81	84	83	89	94	85	86	5
SP_85 (km/h)	90	90	94	92	91	101	93	94	4
%EXT_I	7,9%	29,2%	2,1%	3,8%	10,4%	7,3%	50,3%	11,7%	19,4%
%EXT_UZ	23%	87%	1%	1%	0%	0%	0%	7%	24%
EXT_C (m)	320	220	41	466	486	471	270	321	264
CL_C	2,3	1,8	0,1	2,2	3,0	2,3	1,7	1,8	1,5
CL_G	0,3	0,0	0,1	0,3	0,8	0,6	0,2	0,4	0,4
A_PREC (mm)	1058	735	591	693	1669	490	722	881	461
Nº of segments	19	15	63	38	55	39	25		

RESULTS

MODELLING THE EXPECTED NUMBER OF ROAD ACCIDENTS (I)

• Two different assumptions:

JISBOA 201

- In each road environment, segments present homogeneous traffic conditions, road layout and precipitation, and regression was done with only one explanatory variable, the IFI: RE_IFI
- In defining road environments, some characteristics were dominant, leading to some heterogeneity among the other variables. For this reason, the regression was made by introducing other explanatory variables into the model (i.e., the same variables used in the cluster analysis) – RE_MULT

```
\begin{split} N_{accid}/km &= TRAF_{ACUM_{1}} \\ &\times \exp\left(\beta_{0} + \beta_{1} \times IFI_{i} + \beta_{2} \times \%H_{TRAF_{i}} + \beta_{3} \times AV\_SP_{i} + \beta_{4} \times SP\_85_{i} + \beta_{5} \\ &\times \%EXT\_UZ_{i} + \beta_{6} \times \%EXT\_I_{i} + \beta_{7} \times EXT\_C_{i} + \beta_{8} \times CL\_C_{i} + \beta_{9} \times CL\_G_{i} \\ &+ \beta_{10} \times A\_PREC_{i}) \end{split}
```

RESULTS

MODELLING THE EXPECTED NUMBER OF ROAD ACCIDENTS (II)

World Meeting

LISBOA 2010



RESULTS

Sharing the road

EVALUATION OF THE INFLUENCE OF PAVEMENT SURFACE CHARACTERISTICS ON ACCIDENT OCCURRENCE

- The influence of surface characteristics on accident occurrence was evaluated by analysing the coefficients associated with the explanatory variable IFI and measuring the impact that a change in IFI produces in the expected number of accidents.
- From this analysis, it was possible to conclude that there are, basically, three environments (E_i) where the pavement properties significantly, yet distinctly, influence the occurrence of accidents:
 - E_1 : Rural environment with a heavy presence of urban characteristics RE1 and RE2;
 - E₂: Environment characterised by a considerable predominance of intersections in a rural environment RE7;
 - E_3 : Environment with curved segments, high longitudinal gradients and average speed higher than the tolerable speed RE6.

RESULTS ESTABLISHING THRESHOLD VALUES FOR THE INTERNATIONAL FRICTION INDEX, SKID RESISTANCE AND TEXTURE DEPTH

JISBOA 201

	Minimum Values / Safety Values					
	IFI	Skid Resistance	Texture depth (mm)			
E1	20 / 25	40 / 50	0,4 / 0,5			
E ₂	25 / 28	45 / 55	0,4 / 0,5			
E₃	30 / 33	50 / 60	0,5 / 0,6			



CONCLUSIONS (I)

- A further scientific attempt to establish relationships between functional characteristics of pavement and road accidents by using a set of roads selected from the Portuguese road network.
- The cluster analysis used to identify different road environments is presented as innovative and a valid alternative for choosing the segments to be used in road accident prediction models.
- Weaknesses of cluster analysis: the groups formed are not, in most cases, completely homogeneous and there is some variation of characteristics within the same group, even if the variation within the group is less than between groups.





CONCLUSIONS (II)

- Problems with statistical significance, over-dispersion and reliability of accident data took place during the calibration process.
- Results show that road environments where braking manoeuvres are more common (E₁ and E₂) or those with small radii of curvature and high speeds (E₃) require higher skid resistance and texture depth levels.
- The Portuguese Highways Agency recently recognised the importance of research studies to support the development of maintenance programmes for surface characteristics to be incorporated into pavement management systems. This work seeks to contribute a set of values established according to safety criteria for skid resistance and texture depth maintenance.



Evaluation of road safety in Portugal: a case study analysis THANK YOU

<u>acapote@civil.ist.utl.pt</u> <u>neves@civil.ist.utl.pt</u>